

## Product data sheet

### Characteristics

## 3025-VW

Clipsal Iconic, switched socket, 2 switch & 2 socket, horiz, 10 A, Vivid White



### Main

|                            |                     |
|----------------------------|---------------------|
| Range                      | Clipsal Iconic      |
| Product or component type  | Switched socket     |
| Device presentation        | Complete product    |
| Outlet poles configuration | 2P + E with shutter |
| Outlet standard            | Australian          |

### Complementary

|                                |                                                                                                                                                                                            |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device mounting                | Flush                                                                                                                                                                                      |
| Number of power socket outlets | 2                                                                                                                                                                                          |
| Number of rocker               | 2                                                                                                                                                                                          |
| Outlet standard description    | With earthing contact                                                                                                                                                                      |
| Outlet standard                | Australian/New Zealand                                                                                                                                                                     |
| Ground lug position            | Straight 180° position                                                                                                                                                                     |
| Fixing mode                    | By screw                                                                                                                                                                                   |
| Installation direction         | Horizontal                                                                                                                                                                                 |
| Colour                         | Vivid white (VW)                                                                                                                                                                           |
| Surface finish                 | Matt                                                                                                                                                                                       |
| Type of packing                | Polybag                                                                                                                                                                                    |
| Quantity per set               | Set of 10                                                                                                                                                                                  |
| Sale per indivisible quantity  | 1                                                                                                                                                                                          |
| Rated current                  | 10 A at 250 V AC 50 Hz                                                                                                                                                                     |
| Electrical durability          | 12000 cycles                                                                                                                                                                               |
| Connections - terminals        | 3 screw terminals                                                                                                                                                                          |
| Screwdriver shape              | Philips No 2<br>Square drive no 1 (SQ1)                                                                                                                                                    |
| Clamping connection capacity   | 1 x 2.5...4 x 2.5 mm <sup>2</sup> for rigid cable(s)<br>1 x 2.5...4 x 2.5 mm <sup>2</sup> for stranded cable(s)<br>1 x 2.5...4 x 2.5 mm <sup>2</sup> for flexible cable(s)                 |
| Wire stripping length          | 16 mm                                                                                                                                                                                      |
| Material                       | PC (polycarbonate): fixing frame<br>PP (polypropylene): rocker<br>POM (polyoxymethylene): shutter<br>PC (polycarbonate): cover frame<br>ABS (acrylonitrile butadiene-styrene): cover frame |
| Height                         | 78 mm                                                                                                                                                                                      |
| Width                          | 120 mm                                                                                                                                                                                     |
| Depth                          | 27 mm                                                                                                                                                                                      |
| Embedding depth                | 18 mm                                                                                                                                                                                      |
| Net weight                     | 0.116 kg                                                                                                                                                                                   |

## Environment

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | 0...45 °C   |
| Relative humidity                     | 10...95 %   |
| Standards                             | AS/NZS 3112 |
| Product certifications                | RCM         |

## Packing Units

|                  |            |
|------------------|------------|
| Package 1 Weight | 121.000 g  |
| Package 1 Height | 40.000 mm  |
| Package 1 width  | 80.000 mm  |
| Package 1 Length | 120.000 mm |

## Offer Sustainability

|                            |                                                                                                                                  |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                            |
| REACH Regulation           |  <a href="#">REACH Declaration</a>              |
| REACH free of SVHC         | Yes                                                                                                                              |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes                                                                                                                              |
| Mercury free               | Yes                                                                                                                              |
| RoHS exemption information |  <a href="#">Yes</a>                            |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>         |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |